


Door Phone

For PBX

PBX Door Phone



IP or WiFi Camera



-  **PBX Connection**
-  **Modularity**
-  **External Case anti vandalism**
-  **Wireless connection - DECT (option)**

The Door Phone Multi companies, simple, modular, and evolutionary *...

This Door Phone conceived around a principal module is evolutionary to 64 keys, you can add others modules as camera and also a DECT module to make the system wireless.

The connection behind an analogue FxS of PABX makes it very attractive for small companies or Soho as well as building with several companies. Its modularity allows a great flexibility in use, installation and of evolution. Call the company through a code if need be.

Programming is done through Windows software; very easy for update or any modification of settings. An external power supply makes modules backlit, and an anti system moisture preserves the keys in time.

A function allows to forward calls to an external number, or mobile, and with a special code you will be able to make outgoing calls through the land line of the company called.

Benefits

- Digital keyboard for call with preset code
- An FxS analogue extension is enough for use
- Modular system from 1 to 64 keys extension PABX
- Works in DTMF mode and Decimal (<= 16 digits/button)
- Programming software included (Windows)
- Possibility of controlling two different relays
- External power supply for door command (12 volts)
- External case anti vandalism
- Back lightened case with heating system
- Flashing, pause, tones settings customisable.
- Modules camera, keyboards for names, numeric keyboards, available on ask.
- A DECT module to make the product Wireless *
- Remote configuration
- Can switch to different possibilities (camera, switch on...)
- Switch to night/ Day or 2 groups
- Contact to earth to protect against antistatic electricity
- Selectable time for dialling before pick up.
- IP or IP WiFi camera

* Option



Models

- Link Door Phone 2 buttons (Main module)
- Link Door Phone Keypad (Additional module)
- Link Door Phone IP or WiFi IP camera (Additional module)
- Link Door names with 4 buttons (Additional module) back lighted

Features

Settings

- Through DTMF or PC
 - > **Remote management through PSTN**

Power supply


- 12 volts \sim /= (for light and door)
- Module is powered buy analogue line

Environment

- Storage Temperature range: $-20^{\circ}\text{C}/+70^{\circ}\text{C}$
- Operating Temperature range: $-20^{\circ}\text{C}/+70^{\circ}\text{C}$
- Humidity: 10% to 80% at 30°C

Accessories

- Cases for surface mounted
- Cases for embedded mounted
- Module with labels for companies' names
- DECT Module for wireless connection



Complete module



Base embedded



Surface mounted

Surface mounted or embedded

Main Module

